

SHEATHING  
WITH VAPOR  
BARRIER

WOOD SHINGLES  
OR SIDING

PRESSURE TREATED  
FURRING STRIPS,  
FASTEN TO  
REDDI-FORM BLOCK

FLOOR DECK AND  
FRAMING

BLOCKING BEYOND  
ANCHOR BOLT

PRESSURE TREATED  
2x10

#3 HORIZONTAL REBAR  
AS REQUIRED

#4 VERTICAL REBAR  
AS REQUIRED

3000 P.S.I. CONCRETE


REDDI-FORM BLOCK

15 MINUTE THERMAL  
BARRIER

WOOD SIDING EXTERIOR  
FLOOR & FOUNDATION WALL JUNCTION  
W/ WOOD FRAMING

W2

1" = 1'-0"



**ReddiForm, Inc.**

DUE TO VARIANCES IN LOCAL CODES, ALL DETAILS SHALL BE CONSTRUCTED IN ACCORDANCE WITH LOCAL CODES REGARDLESS OF DETAIL CONSTRUCTION SHOWN IN DRAWING. REDDI-FORM RESERVES THE RIGHT TO CHANGE INFORMATION SHOWN WITHOUT NOTICE.

|                 |             |
|-----------------|-------------|
| DRAWN BY:       | CHECKED BY: |
| SCALE: 1"=1'-0" |             |
| DATE: 6/25/96   |             |
| JOB NUMBER      | SHEET       |
| REDDI-FORM      | W2          |